Truly Enlightening

ARRI LIGHTING PRODUCT RANGE

STUDIO

LED

L-SERIES

L5-DT LED Fresnel 115 W

Color:	L5.0001002*	L5.0001000*
Hanging:	L5.0001003*	L5.0001001*
P.O.:	L5.0001004**	L5.0001006**
Stand-Mount:	L5.0001005***	

Technical Data: Size (HxWxL): MAIN: 321 x 278 x 280 mm; P.O.: 315 x 270 x 280 mm. Packed Size: 470 x 400 x 410 mm. Weight: MAIN: 5.1 kg; P.O.: 7 kg. Protection Class: IP 20. Lens Ø: 137 mm. Color Temperature: 5600 K - 6500 K. Mounting: 16 mm / 28 mm Combo Pin. Certifications: CE, CB, GS, UNRTL, Fcc, ISO9001:2000

Accessories: 4-leaf Barndoor LZ.7047.0; 4-leaf Barndoor (black/silver) LZ.7047.1; 4-leaf Barndoor LZ.7050.0; Fiber Frame LZ.9960.0; Soft Diffuser LZ.9999.0; Spot Reflector LZ.9998.0; Softbox Adapter LZ.9980.0; 1.5 m power/ON/Schuko ends cord L0.0001040; 1.5 m power/ON/Schuko cord with 1 m power/ON/Edison cord L0.0001041; 1.5 m power/ON/Schuko cord with 1 m power/ON/Edison cord L0.0001487; Dimmer LZ.9990.0

* with 1.5 m power/ON/Fare ends cord
** with 1 m power/ON/Schuko cord
*** with 1 m power/ON/Edison cord

L5-TE LED Fresnel 115 W

Color:	L5.0001102*	L5.0001101*
Hanging:	L5.0001103*	L5.0001104*
P.O.:	L5.0001105**	L5.0001107**
Stand-Mount:	L5.0001106***	L5.0001108***

Technical Data: Size (HxWxL): MAIN: 321 x 278 x 280 mm; P.O.: 315 x 270 x 280 mm. Packed Size: 470 x 400 x 410 mm. Weight: MAIN: 5.1 kg; P.O.: 7 kg. Protection Class: IP 20. Lens Ø: 137 mm. Color Temperature: 2800 K - 6500 K. Mounting: 16 mm / 28 mm Combo Pin. Certifications: CE, CB, GS, UNRTL, Fcc, ISO9001:2000

Accessories: 4-leaf Barndoor LZ.7047.0; 4-leaf Barndoor (black/silver) LZ.7047.1; 4-leaf Barndoor LZ.7050.0; Fiber Frame LZ.9960.0; Soft Diffuser LZ.9999.0; Spot Reflector LZ.9998.0; Softbox Adapter LZ.9980.0; 1.5 m power/ON/Fare ends cord L0.0001040; 1.5 m power/ON/Schuko cord with 1 m power/ON/Edison cord L0.0001041; 1.5 m power/ON/Schuko cord with 1 m power/ON/Edison cord L0.0001487; Dimmer LZ.9990.0

* with 1.5 m power/ON/Fare ends cord
** with 3 m power/ON/Schuko cord
*** with 7 m power/ON/Edison cord

L5-C LED Fresnel 115 W

Color:	L5.0001001*	L5.0001004*
Hanging:	L5.0001002*	L5.0001003*
P.O.:	L5.0001004**	
Stand-Mount:	L5.0001005***	

Technical Data: Size (HxWxL): MAIN: 321 x 278 x 280 mm; P.O.: 315 x 270 x 280 mm. Packed Size: 470 x 400 x 410 mm. Weight: MAIN: 5.1 kg; P.O.: 7 kg. Protection Class: IP 20. Lens Ø: 137 mm. Color Temperature: 5600 K - 6500 K. Mounting: 16 mm / 28 mm Combo Pin. Certifications: CE, CB, GS, UNRTL, Fcc, ISO9001:2000

Accessories: 4-leaf Barndoor LZ.7047.0; 4-leaf Barndoor (black/silver) LZ.7047.1; 4-leaf Barndoor LZ.7050.0; Fiber Frame LZ.9960.0; Soft Diffuser LZ.9999.0; Spot Reflector LZ.9998.0; Softbox Adapter LZ.9980.0; 1.5 m power/ON/Fare ends cord L0.0001040; 1.5 m power/ON/Schuko cord with 1 m power/ON/Edison cord L0.0001041; 1.5 m power/ON/Schuko cord with 1 m power/ON/Edison cord L0.0001487; Dimmer LZ.9990.0

* with 1.5 m power/ON/Fare ends cord
** with 3 m power/ON/Schuko cord
*** with 7 m power/ON/Edison cord

L-SERIES

L7-DT LED Fresnel 160 W

Color:	L1.0120002*	L1.0120006*
Hanging:	L1.0120003*	L1.0120007*
P.O.:	L1.0120004*	L1.0120008*
Stand-Mount:	L1.0120005*	
	L1.0120009**	
	L1.0120010**	
	L1.0120011**	
	L1.0120012**	

Technical Data: Size (HxWxL): Hybrid: 384 x 374 x 423 mm; Active: 345 x 374 x 423 mm. Packed Size: 570 x 500 x 510 mm. Weight: Hybrid: MAIN 10.9 kg, P.O. 12.5 kg; Active: MAIN 8.2 kg, P.O. 9.8 kg. Protection Class: IP 20. Lens Ø: 175 mm. Color Temperature: 5600 K - 6500 K. Mounting: 16 mm / 28 mm Combo Pin. Certifications: CE, CB, GS, UNRTL, Fcc, ISO9001:2000

Accessories: 4-leaf Barndoor LZ.7048.0; 4-leaf Barndoor LZ.7048.1; 4-leaf Barndoor LZ.7050.0; Fiber Frame LZ.9960.0; Soft Diffuser LZ.9999.0; Spot Reflector LZ.9998.0; Softbox Adapter LZ.9980.0; 1.5 m power/ON/Fare ends cord L0.0001040; 1.5 m power/ON/Schuko cord with 1 m power/ON/Edison cord L0.0001041; Dimmer LZ.9990.0

* **Hybrid:** allows for both active and passive cooling (employs a heat sink to cool the L7 via natural air flow for silent operation)
** **Active:** allows only for active cooling (employs a compact, low noise forced air assembly to cool the L7)

L7-TT LED Fresnel 160 W

Color:	L1.0120101*	L1.0120105*
Hanging:	L1.0120102*	L1.0120106*
P.O.:	L1.0120103*	L1.0120107*
Stand-Mount:	L1.0120104*	L1.0120108*
	L1.0120109**	
	L1.0120110**	
	L1.0120111**	
	L1.0120112**	

Technical Data: Size (HxWxL): Hybrid: 384 x 374 x 423 mm; Active: 345 x 374 x 423 mm. Packed Size: 570 x 500 x 510 mm. Weight: Hybrid: MAIN 10.9 kg, P.O. 12.5 kg; Active: MAIN 8.2 kg, P.O. 9.8 kg. Protection Class: IP 20. Lens Ø: 175 mm. Color Temperature: 2800 K - 3800 K. Mounting: 16 mm / 28 mm Combo Pin. Certifications: CE, CB, GS, UNRTL, Fcc, ISO9001:2000

Accessories: 4-leaf Barndoor LZ.7048.0; 4-leaf Barndoor LZ.7048.1; 4-leaf Barndoor LZ.7050.0; Fiber Frame LZ.9960.0; Soft Diffuser LZ.9999.0; Spot Reflector LZ.9998.0; Softbox Adapter LZ.9980.0; 1.5 m power/ON/Fare ends cord L0.0001040; 1.5 m power/ON/Schuko cord with 1 m power/ON/Edison cord L0.0001041; 1.5 m power/ON/Schuko cord with 1 m power/ON/Edison cord L0.0001487; Dimmer LZ.9990.0

* with 1.5 m power/ON/Fare ends cord
** with 3 m power/ON/Schuko cord
*** with 7 m power/ON/Edison cord

* **Hybrid:** allows for both active and passive cooling (employs a heat sink to cool the L7 via natural air flow for silent operation)
** **Active:** allows only for active cooling (employs a compact, low noise forced air assembly to cool the L7)

CASTER SERIES

LOCASTER 2 PLUS 35 W

Color: ■
Sidecard Control: L0.0001320
Kits: L0.0002330; L0.0002331

Technical Data: Size (HxWxL): 96 x 70 x 218 mm. Packed Size: 135 x 135 x 235 mm. Weight: 1.2 kg. Shipping Weight: 1.2 kg. Protection Class: IP 20. Mounting: Thread 3/8". Power Consumption: 35 W. Tunable White: 2800 K - 6500 K. Tunable Green: (-7) - (+7). Certifications: CE (CB, FCC in progress)

Accessories: LZ.3000.0 Caster Power Supply; LZ.3000.1 Caster Power Supply 230 W - Schuko; LZ.3000.2 Caster Power Supply 230 W - Schuko; LZ.3000.3 Caster Battery Charger; LZ.3000.4 Caster Battery Charger; Car Power Adapter LZ.7707.0; Caster Strap LZ.3000.5; Foldable Intensifier LZ.3000.6; 4-Pin Battery Extension Cable LZ.7475.0; Adapter Stud 16/135 mm LZ.3000.8; Power DMX Extension Cable LZ.3000.9; Power DMX Extension Cable LZ.3017.1

BROADCASTER 2 PLUS 35 W

Color: ■
Power DMX: L1.0002305

Technical Data: Size (HxWxL): 96 x 70 x 218 mm. Packed Size: 115 x 80 x 235 mm. Weight: 0.96 kg. Shipping Weight: 1.2 kg. Protection Class: IP 20. Mounting: Thread 3/8". Power Consumption: 35 W. Tunable White: 2800 K - 6500 K. Tunable Green: (-7) - (+7). Certifications: CE (CB, FCC in progress)

Accessories: LZ.3000.0 Caster Power Supply; LZ.3000.1 Caster Power Supply 230 W - Schuko; LZ.3000.2 Caster Power Supply 230 W - Schuko; LZ.3000.3 Caster Battery Charger; LZ.3000.4 Caster Battery Charger; Car Power Adapter LZ.3001.0; Caster Strap LZ.3000.5; Foldable Intensifier LZ.3000.6; Power DMX Extension Cable LZ.3000.9; Power DMX Extension Cable LZ.3017.1; Adapter Stud 16/135 mm LZ.3000.8

M-SERIES

ARRIMAX 18/12 18000 W

Color: ■
Manual: L3.37050.B

Technical Data: Size (HxWxL): 1001 x 784 x 342 mm. Packed Size: 1135 x 1050 x 1170 mm. Weight: 65.5 kg. Shipping Weight: 68.5 kg (with pallet). Protection Class: IP 23. Lamp: Metal Halide 18000 W/SE; Metal Halide 12000 W/SE; CDI/CDQ6. Base: 828 mm. UV Glass: 625 mm. Certifications: CE, CB, GS, UNRTL

Accessories: Spare Set LZ.7115.0; Spot Reflector LZ.7040.0; Dryer LZ.7041.0

M90 3000 W

Color: ■
Manual: L3.37400.B

Technical Data: Size (HxWxL): 847 x 713 x 716 mm. Packed Size: 930 x 790 x 910 mm. Weight: 70 kg. Shipping Weight: 75 kg (with pallet). Protection Class: IP 23. Lamp: Metal Halide 3000 W/SE; Metal Halide 6000 W/SE; CDQ6. Base: 828 mm. UV Glass: 625 mm. Certifications: Spoon 28 mm; CE, CB, GS, UNRTL

Accessories: Spare Set LZ.7056.0; Spot Reflector LZ.7040.0; Softbox Adapter LZ.7058.0

M40 4000 W

Color: ■
Manual: L3.37450.B

Technical Data: Size (HxWxL): 670 x 402 x 511 mm. Packed Size: 800 x 600 x 695 mm. Weight: 40 kg. Shipping Weight: 45 kg (with pallet). Protection Class: IP 23. Lamp: Metal Halide 4000 W/SE; Metal Halide 2500 W/SE; CDQ6. Base: 828 mm. UV Glass: 625 mm. Certifications: Spoon 28 mm; CE, CB, GS, UNRTL

Accessories: 4-leaf Barndoor LZ.7050.0; Fiber Frame LZ.9960.0; Soft Diffuser LZ.9999.0; Spot Reflector LZ.9998.0; Spot Set LZ.7115.0; Dryer LZ.7041.0

M18 1000 W

Color: ■
Manual: L3.37600.B

Technical Data: Size (HxWxL): 567 x 367 x 388 mm. Packed Size: 690 x 510 x 555 mm. Weight: 19.5 kg. Shipping Weight: 22 kg (with pallet). Protection Class: IP 23. Lamp: Metal Halide 1000 W/SE; Metal Halide 1200 W/SE; CDQ6. Base: 250 mm. UV Glass: 250 mm. Certifications: Spoon 28 mm; CE, CB, GS, UNRTL

Accessories: 4-leaf Barndoor LZ.7050.0; 4-leaf Barndoor LZ.7050.1; Fiber Frame LZ.9960.0; Soft Diffuser LZ.9999.0; Spot Reflector LZ.9998.0; Spot Set LZ.7115.0; Dryer LZ.7041.0

M8 800 W

Color: ■
Manual: L3.37200.B

Technical Data: Size (HxWxL): 320 x 344 x 311 mm. Packed Size: 440 x 400 x 480 mm. Weight: 9.5 kg. Shipping Weight: 11 kg. Protection Class: IP 23. Lamp: Metal Halide 800 W/SE; CDQ. Base: 250 mm. UV Glass: 250 mm. Certifications: Spoon 28 mm; CE, CB, GS, UNRTL

Accessories: Soft Reflector LZ.7077.0; Spot Reflector LZ.7080.0; Softbox Adapter LZ.7058.0; Frosted Glass LZ.7036.0

TRUE BLUE D

TRUE BLUE D40 4000 W

Color: ■
Manual: L3.34600.B; L3.34605.B

Technical Data: Size (HxWxL): 727 x 524 x 403 mm. Packed Size: 860 x 650 x 770 mm. Weight: 13.5 kg. Shipping Weight: 15 kg (with pallet). Protection Class: IP 23. Lamp: Metal Halide 4000 W/SE. Lens Ø: 300 mm. Mounting: Spigot 28 mm. Certifications: CE, CB, GS, UNRTL

Accessories: 4-leaf Barndoor LZ.0110.0; 4-leaf Barndoor LZ.0110.1; Fiber Frame LZ.0960.0; Soft Diffuser LZ.0962.0; Softbox Adapter LZ.0125.0; Dimmer LZ.0125.0

TRUE BLUE D25 2500 W

Color: ■
Manual: L3.33670.B; L3.33675.B

Technical Data: Size (HxWxL): 643 x 464 x 390 mm. Packed Size: 760 x 610 x 650 mm. Weight: 14 kg. Shipping Weight: 16 kg (with pallet). Protection Class: IP 23. Lamp: Metal Halide 2500 W/SE. Lens Ø: 250 mm. Mounting: Spigot 28 mm. Certifications: CE, CB, GS, UNRTL

Accessories: 4-leaf Barndoor LZ.1800.0; 4-leaf Barndoor LZ.1800.1; Fiber Frame LZ.0960.0; Soft Diffuser LZ.0962.0; Softbox Adapter LZ.0125.0; Dimmer LZ.0975.0

TRUE BLUE D12 1200 W

Color: ■
Manual: L3.33730.B; L3.33735.B

Technical Data: Size (HxWxL): 511 x 375 x 325 mm. Packed Size: 660 x 450 x 650 mm. Weight: 12 kg. Shipping Weight: 13.5 kg. Protection Class: IP 23. Lamp: Metal Halide 1200 W/SE; CDQ6. Lens Ø: 175 mm. Mounting: Spigot 28 mm. Certifications: CE, CB, GS, UNRTL

Accessories: 4-leaf Barndoor LZ.7800.0; 4-leaf Barndoor LZ.7800.1; Fiber Frame LZ.7800.2; Soft Diffuser LZ.7824.0; Softbox Adapter LZ.7800.3; Dimmer LZ.7800.5

TRUE BLUE D5 575 W

Color: ■
Manual: L3.33770.B; L3.33775.B

Technical Data: Size (HxWxL): 359 x 327 x 223 mm. Packed Size: 390 x 390 x 390 mm. Weight: 6.1 kg. Shipping Weight: 7 kg. Protection Class: IP 23. Lamp: Metal Halide 575 W/SE; CDQ. Lens Ø: 150 mm. Mounting: Spigot 28 mm. Certifications: CE, CB, GS, UNRTL

Accessories: 4-leaf Barndoor LZ.7800.0; 4-leaf Barndoor LZ.7800.1; Fiber Frame LZ.7800.2; Soft Diffuser LZ.7824.0; Softbox Adapter LZ.7800.3; Dimmer LZ.7800.5

ARRI FRESNEL (DAYLIGHT)

ARRI DAYLIGHT 18/12 18000 W

Color: ■
Manual: L1.71600.B

Technical Data: Size (HxWxL): 1008 x 1040 x 825 mm. Packed Size: 1135 x 1170 x 1000 mm. Weight: 69.5 kg. Shipping Weight: 72.5 kg (with pallet). Protection Class: IP 23. Lamp: Metal Halide 18000 W/SE; Metal Halide 12000 W/SE; CDQ. Base: 625 mm. UV Glass: 625 mm. Certifications: CE, CB, GS, UNRTL

Accessories: 4-leaf Barndoor LZ.7100.0; Spot Set LZ.7115.0

COMPACT

ARRI COMPACT 12000 BAYT 12000 W

Color: ■
Manual: L1.70700.B

Technical Data: Size (HxWxL): 872 x 582 x 690 mm. Packed Size: 895 x 720 x 790 mm. Weight: 47.2 kg. Shipping Weight: 79.5 kg (with pallet). Protection Class: IP 23. Lamp: Metal Halide 12000 W/SE; CDQ6. Base: 625 mm. UV Glass: 625 mm. Certifications: Spoon 28 mm; CE, CB, GS, UNRTL

Accessories: 4-leaf Barndoor LZ.7470.0

ARRI COMPACT 6000 Plus 6000 W

Color: ■
Manual: L1.70720.B

Technical Data: Size (HxWxL): 790 x 694 x 590 mm. Packed Size: 790 x 730 x 790 mm. Weight: 38.5 kg. Shipping Weight: 45 kg (with pallet). Protection Class: IP 23. Lamp: Metal Halide 6000 W/SE; CDQ. Base: 625 mm. UV Glass: 625 mm. Certifications: Spoon 28 mm; CE, CB, GS, UNRTL

Accessories: 4-leaf Barndoor LZ.0160.0; Fiber Frame LZ.0160.0; Soft Diffuser LZ.0160.0; Spot Set LZ.0160.0

ARRI COMPACT 200 200 W

Color: ■
Manual: L1.70800.B

Technical Data: Size (HxWxL): 294 x 218 x 193 mm. Packed Size: 360 x 260 x 290 mm. Weight: 3.1 kg. Shipping Weight: 5 kg. Protection Class: IP 23. Lamp: Metal Halide 200 W/SE. Lens Ø: 112 mm. Mounting: Spigot 16 mm. Certifications: CE

Accessories: 4-leaf Barndoor LZ.7040.0; Fiber Frame LZ.7040.0; Soft Diffuser LZ.7040.0; Spot Set LZ.7040.0; Dimmer LZ.7040.1

COMPACT THEATRE

ARRI COMPACT THEATRE 4000 4000 W

Color: ■ theatre grey
Manual: L1.74610.B
Motorized*: L1.74620.B

Technical Data: Size (HxWxL): 895 x 656 x 456 mm. Packed Size: 895 x 720 x 775 mm. Weight: 27 kg. Shipping Weight: 32 kg. Protection Class: IP 23. Lamp: Metal Halide 4000 W/SE; CDQ. Lens Ø: 320 mm. Mounting: Spigot 28 mm. Certifications: CE, CB, GS, UNRTL

Accessories: 4-leaf Barndoor LZ.0162.0; Fiber Frame LZ.0159.0

ARRI COMPACT THEATRE 2500 2500 W

Color: ■ theatre grey
Manual: L1.73000.B
Motorized*: L1.73050.B

Technical Data: Size (HxWxL): 770 x 590 x 396 mm. Packed Size: 770 x 610 x 620 mm. Weight: 27 kg. Shipping Weight: 32 kg. Protection Class: IP 23. Lamp: Metal Halide 2500 W/SE; CDQ. Lens Ø: 320 mm. Mounting: Spigot 28 mm. Certifications: CE, CB, GS, UNRTL

Accessories: 4-leaf Barndoor LZ.0050.0; Fiber Frame LZ.0010.0

* MB-ready version is supplied with the necessary mountings for a motorized stirrup

ARRISUN

ARRISUN 120 12000 W

Color: ■
Manual: L1.71800.B

Technical Data: Size (HxWxL): 948 x 760 x 850 mm. Packed Size: 975 x 870 x 950 mm. Weight: 49.6 kg. Shipping Weight: 54 kg (with pallet). Protection Class: IP 23. Lamp: Metal Halide 12000 W/SE; CDQ. Lens Ø: 500 mm. Mounting: Spigot 28 mm. Certifications: CE, CB, GS, UNRTL

Accessories: 4-leaf Barndoor LZ.0970.0; Spot Set LZ.0970.0; 1 Lens Set. 500 mm incl. case LZ.0897.0

ARRISUN 60 6000 W

Color: ■
Manual: L1.71880.B

Technical Data: Size (HxWxL): 872 x 582 x 690 mm. Packed Size: 895 x 720 x 790 mm. Weight: 47 kg. Shipping Weight: 52 kg (with pallet). Protection Class: IP 23. Lamp: Metal Halide 6000 W/SE; CDQ6. Lens Ø: 420 mm. Mounting: Spigot 28 mm. Certifications: CE, CB, GS, UNRTL

Accessories: 4-leaf Barndoor LZ.0160.0; 1 Lens Set. 420 mm incl. case LZ.7480.0; 1 Lens Set. 285 mm incl. case LZ.7480.2

AS 40 4000 W

Color: ■
Lamphead: L1.71900.B

Technical Data: Size (HxWxL): 723 x 471 x 590 mm. Packed Size: 860 x 650 x 870 mm. Weight: 22.2 kg. Shipping Weight: 25 kg (with pallet). Protection Class: IP 23. Lamp: Metal Halide 4000 W/SE; Metal Halide 2500 W/SE; CDQ. Lens Ø: 300 mm. Mounting: Spigot 28 mm. Certifications: CE, CB, GS, UNRTL

Accessories: 4-leaf Barndoor LZ.0180.0; 4-leaf Barndoor LZ.0180.1; Fiber Frame LZ.0960.0; Soft Diffuser LZ.0962.0; Softbox Adapter LZ.0125.0; Dimmer LZ.0975.0

AS 18 1800 W

Color: ■
Manual: L1.71950.B

Technical Data: Size (HxWxL): 595 x 367 x 416 mm. Packed Size: 690 x 510 x 555 mm. Weight: 12.5 kg. Shipping Weight: 15 kg (with pallet). Protection Class: IP 23. Lamp: Metal Halide 1800 W/SE; Metal Halide 1200 W/SE; CDQ. Lens Ø: 250 mm. Mounting: Spigot 28 mm. Certifications: Spoon 28 mm; CE, CB, GS, UNRTL

Accessories: 4-leaf Barndoor LZ.7050.0; 4-leaf Barndoor LZ.7050.1; Fiber Frame LZ.9960.0; Soft Diffuser LZ.9999.0; Spot Set LZ.7115.0; Dryer LZ.7041.0

ARRISUN 5 575 W

Color: ■
Manual: L1.71950.B

Technical Data: Size (HxWxL): 358 x 272 x 310 mm. Packed Size: 390 x 490 x 390 mm. Weight: 5.8 kg. Shipping Weight: 7 kg. Protection Class: IP 23. Lamp: Metal Halide 575 W/SE; CDQ. Lens Ø: 175 mm. Mounting: Spigot 28 mm. Certifications: CE

Accessories: 4-leaf Barndoor LZ.7800.0; 4-leaf Barndoor LZ.7800.1; Fiber Frame LZ.7800.2; Soft Diffuser LZ.7824.0; Softbox Adapter LZ.7800.3; Dimmer LZ.7800.5; Spot Set LZ.7040.0; 1 Lens Set. 175 mm LZ.7800.2

ARRISUN 2 200 W

Color: ■
Manual: L1.27630.B

Technical Data: Size (HxWxL): 250 x 204 x 267 mm. Packed Size: 290 x 235 x 280 mm. Weight: 2.3 kg. Shipping Weight: 3 kg. Protection Class: IP 23. Lamp: Metal Halide 200 W/SE. Lens Ø: 112 mm. Mounting: Socket 16 mm. Certifications: CE

Accessories: 4-leaf Barndoor LZ.0960.0; 4-leaf Barndoor LZ.0960.1; Fiber Frame LZ.0960.0; Soft Diffuser LZ.0962.0; Spot Set LZ.0960.0

ARRI LENS COLOR CODES

Spot Lens	Blue
Narrow Flood Lens (small rectangles)	Black
Flood Lens (large rectangles)	Green
Super Flood Lens (hexagonals)	Red
Frosted Spot Lens	Yellow
Frosted Flood Lens	Silver

ARRISUN EVENT

ARRISUN 18 EVENT 1800 W

Color: ■
Manual: L1.37591.E; L1.37595.E

Technical Data: Size (HxWxL): 543 x 384 x 276 mm. Packed Size: 550 x 510 x 590 mm. Weight: 10.5 kg. Shipping Weight: 12 kg. Protection Class: IP 23. Lamp: Metal Halide 1800 W/SE. Lens Ø: 250 mm. Mounting: Spigot 28 mm. Certifications: CE, CB, GS, UNRTL

Accessories: 4-leaf Barndoor, silver LZ.7001.0; 4-leaf Barndoor, black LZ.7001.1; 4-leaf Barndoor LZ.7050.0; Spot Lens LZ.7080.0; Narrow Flood Lens LZ.7080.0; Flood Lens LZ.7080.0; Super Flood Lens LZ.7080.0; 4 Lens Set. 125 mm LZ.7080.3; Transmitter Pendant Wireless DMX LZ.7080.5; Receiver Wireless DMX LZ.7080.6; Adapter to ARAM LZ.7020.5

ARRISUN 5 EVENT 575 W

Color: ■
Manual: L1.73671.E; L1.73675.E

Technical Data: Size (HxWxL): 344 x 204 x 206 mm. Packed Size: 470 x 380 x 320 mm. Weight: 6.15 kg. Shipping Weight: 8.5 kg. Protection Class: IP 23. Lamp: Metal Halide 575 W/SE. Lens Ø: 180 mm. Mounting: Spigot 28 mm. Certifications: CE

Accessories: 4-leaf Barndoor, silver LZ.7001.0; 4-leaf Barndoor, black LZ.7001.1; 4 Lens Set. 175 mm LZ.7080.3; Transmitter Pendant Wireless DMX LZ.7080.5; Receiver Wireless DMX LZ.7080.6; Adapter to ARAM LZ.7020.5

ARRI LENS COLOR CODES

Spot Lens	Blue
Narrow Flood Lens (small rectangles)	Black
Flood Lens (large rectangles)	Green
Super Flood Lens (hexagonals)	Red
Frosted Spot Lens	Yellow
Frosted Flood Lens	Silver

ARRI X

ARRI X 60 6000 W

Color: ■
Manual: L1.82050.B

Technical Data: Size (HxWxL): 935 x 810 x 400 mm. Packed Size: 775 x 730 x 700 mm. Weight: 32.2 kg. Shipping Weight: 37 kg (with pallet). Protection Class: IP 23. Lamp: Metal Halide 6000 W/SE. Lens Ø: 420 mm. Mounting: Spigot 28 mm. Certifications: CE, CB, GS, UNRTL

Accessories: 4-leaf Barndoor LZ.0180.0; 4-leaf Barndoor LZ.0180.1; Fiber Frame LZ.0180.0; Soft Diffuser LZ.0180.0; Spot Set LZ.0180.0

ARRI X 40/25 4000 W

Color: ■
Manual: L1.82080.B

Technical Data: Size (HxWxL): 760 x 500 x 290 mm. Packed Size: 820 x 610 x 670 mm. Weight: 27 kg. Shipping Weight: 32 kg. Protection Class: IP 23. Lamp: Metal Halide 4000 W/SE; Metal Halide 2500 W/SE. Lens Ø: 315 x 300 mm. Mounting: Spigot 28 mm. Certifications: CE, CB, GS, UNRTL

Accessories: 4-leaf Barndoor LZ.0740.0; 4-leaf Barndoor LZ.0740.1; Fiber Frame LZ.0740.0; Soft Diffuser LZ.0740.0; Spot Set LZ.0740.0; Adapter/Ballast Ballast 2.5 kW LZ.7746.0

ARRI X 12 1200 W

Color: ■
Manual: L1.82258.B

Technical Data: Size (HxWxL): 619 x 405 x 200 mm. Packed Size: 620 x 610 x 670 mm. Weight: 14 kg. Shipping Weight: 19 kg (with pallet). Protection Class: IP 23. Lamp: Metal Halide 1200 W/SE; CDQ. Lens Ø: 315 x 300 mm. Mounting: Spigot 28 mm. Certifications: CE, CB, GS, UNRTL

Accessories: 4-leaf Barndoor LZ.0770.0; 4-leaf Barndoor LZ.0770.1; Fiber Frame LZ.0770.0; Soft Diffuser LZ.0770.0; Spot Set LZ.0770.0

ARRI X 5 575 W

Color: ■
Manual: L1.82358.B

Technical Data: Size (HxWxL): 550 x 378 x 208 mm. Packed Size: 610 x 410 x 410 mm. Weight: 9 kg. Shipping Weight: 12 kg. Protection Class: IP 23. Lamp: Metal Halide 575 W/SE; CDQ. Lens Ø: 270 x 230 mm. Mounting: Spigot 28 mm. Certifications: CE

Accessories: 4-leaf Barndoor LZ.0810.0; 4-leaf Barndoor LZ.0810.1; Fiber Frame LZ.0810.0; Soft Diffuser LZ.0810.0; Spot Set LZ.0810.0

ARRI X THEATRE

ARRI X 40/25 THEATRE 4000 W

Color: ■ theatre grey
Manual: L1.82618.B

Technical Data: Size (HxWxL): 760 x 500 x 312 mm. Packed Size: 870 x 610 x 620 mm. Weight: 24 kg. Shipping Weight: 29 kg. Protection Class: IP 23. Lamp: Metal Halide 4000 W/SE; Metal Halide 2500 W/SE. Lens Ø: 385 x 400 mm. Mounting: Spigot 28 mm. Certifications: CE, CB, GS, UNRTL

Accessories: 4-leaf Barndoor LZ.0811.0; Adapter for Choke Ballast 2.5 kW LZ.7746.0

DIMENSIONS



Dimensions on this chart are in millimeters and with the fixtures shown. These may differ from figures in other charts in this brochure which uses different definitions.

BALLASTS

LOCATION BALLASTS

12/18 kW ELECTRONIC BALLAST

ER 12/18 kW
Standard: L2.76290.0
DMX: L2.76291.0

Technical Data: Size (HxWxL): 548 x 292 x 506 mm. Weight: 49 kg. Protection Class: IP 22

Accessories: 25 m 12/18 kW Head to Ballast Cable L2.0120.0; 25 m 12/18 kW Head to Ballast Cable L2.0120.4

6/12 kW ELECTRONIC BALLAST

ER 6/12 kW ■ 6/12 kW 115/60-230/50 V AC
Standard: L2.76910.0 ■ 6/12 kW 100-230/50-60 V AC
DMX: L2.76912.0
200 Hz HQI*: L2.76100.0

Technical Data: Size (HxWxL): 490 x 292 x 506 mm. Weight: 42 kg. Protection Class: IP 22

Accessories: 7 m 6/12 kW Head to Ballast Cable L2.7766.0; 15 m 6/12 kW Head to Ballast Cable L2.7766.4; 7 m 200 W Head to Ballast Cable L2.7766.7; 15 m 200 W Head to Ballast Cable L2.7766.8

6/9 kW ELECTRONIC BALLAST

ER 6/9 kW
Standard: L2.76180.0
DMX: L2.76181.0
200 Hz HQI*: L2.76180.9

Technical Data: Size (HxWxL): 490 x 292 x 400 mm. Weight: 42 kg. Protection Class: IP 22

Accessories: 7 m 6/9 kW Head to Ballast Cable L2.7766.0; 15 m 6/9 kW Head to Ballast Cable L2.7766.4; 7 m 6/9 kW Head to Ballast Cable L2.7766.5

6 kW ELECTRONIC BALLAST BABY

EB 6 kW
Standard: L2.76200.0
DMX: L2.76201.0
1000Hz HQI*: L2.76200.9
Schaltbar: ---

Technical Data: Size (HxWxL): 172 x 200 x 335 mm. Weight: 8 kg. Protection Class: IP 21

Accessories: 7 m 5/6/1200/1800 W Head to Ballast Cable L2.7566.0; 15 m 5/6/1200/1800 W Head to Ballast Cable L2.7566.4; 7 m 5/6/1200 W Head to Ballast Cable L2.7566.5; 15 m 5/6/1200 W Head to Ballast Cable L2.7566.6

575/1200 W ELECTRONIC BALLAST

EB 575/1.2 kW
Standard: L2.76625.0
1000Hz HQI*: L2.76625.9
Schaltbar: ---

Technical Data: Size (HxWxL): 186 x 200 x 300 mm (L2.76625.0); 186 x 200 x 335 mm (L2.76625.9). Weight: 8 kg (L2.76625.0); 9 kg (L2.76625.9). Protection Class: IP 22

Accessories: 7 m 5/6/1200 W Head to Ballast Cable L2.7566.0; 15 m 5/6/1200 W Head to Ballast Cable L2.7566.4; 7 m 5/6/1200 W Head to Ballast Cable L2.7566.5; 15 m 5/6/1200 W Head to Ballast Cable L2.7566.6

575/800 W ELECTRONIC BALLAST

EB 575/800 W
Standard: L2.76180.0
1000Hz HQI*: L2.76180.9

Technical Data: Size (HxWxL): 142 x 202 x 334 mm. Weight: 8.5 kg. Protection Class: IP 22

Accessories: 7 m 5/6/1200 W Head to Ballast Cable L2.7566.0; 15 m 5/6/1200 W Head to Ballast Cable L2.7566.4

200 W ELECTRONIC BALLAST

EB 200 W
Standard: L2.76115.0
DMX: L2.76115.9

Technical Data: Size (HxWxL): 134 x 146 x 251 mm. Weight: 2.9 kg. Protection Class: IP 22

Accessories: 7 m 200W Head to Ballast Cable L2.7031.0

* HS stands for High Speed Version

ELECTRONIC LIGHTWEIGHT

400/575 W ELECTRONIC BALLAST

EB 400/575 W 110/230 V
Standard: L2.76260.0
Schaltbar: L2.76260.9

Technical Data: Size (HxWxL): 48 x 155 x 270 mm. Weight: 3 kg. Protection Class: IP 20

Accessories: 7 m 400 W Head to Ballast Cable L2.7860.0; 7 m 400 W Head to Ballast Cable L2.7860.9

125/200 W ELECTRONIC BALLAST

EB 125/200 W 110/230 V
Standard: L2.76010.0

Technical Data: Size (HxWxL): 70 x 130 x 241 mm. Weight: 2.3 kg. Protection Class: IP 20

Accessories: 7 m 125 W Head to Ballast Cable L2.7200.0; 7 m 200 W Head to Ballast Cable L2.7200.9

ELECTRONIC BATTERY

200/400 W ELECTRONIC BATTERY BALLAST

EBB 200/400 W 26-34 VDC
Standard: L2.76276.0

Technical Data: Size (HxWxL): 51 x 155 x 205 mm. Weight: 1.5 kg. Protection Class: IP 20

Accessories: 7 m 400 W Head to Ballast Cable L2.7260.0

125/200 W ELECTRONIC BATTERY BALLAST

EBB 125/200 W 26-34 VDC
Standard: L2.76040.B

Technical Data: Size (HxWxL): 67 x 150 x 158 mm. Weight: 1.2 kg. Protection Class: IP 22

Accessories: 7 m 125 W Head to Ballast Cable L2.7200.0; 7 m 200 W Head to Ballast Cable L2.7200.9

ELECTRONIC BOOSTER

4 kW ELECTRONIC BOOSTER BALLAST

EB 4 kW Booster
Standard: L2.76093.0

Technical Data: Size (HxWxL): 358 x 243 x 450 mm. Weight: 25 kg. Protection Class: IP 22

Accessories: 7 m 4 kW Head to Ballast Cable L2.7562.0; 15 m 4 kW Head to Ballast Cable L2.7562.4; 7 m 4 kW Head to Ballast Cable L2.7562.5

CHOKE

4 kW CHOKE BALLAST

CB 4 kW 220-240 V
DMX: ---
Standard: L2.76870.0

Technical Data: Size (HxWxL): 358 x 365 x 630 mm. Weight: 67 kg. Protection Class: IP 22

Accessories: 7 m 4 kW Head to Ballast Cable L2.7562.0; 15 m 4 kW Head to Ballast Cable L2.7562.4

2.5 kW CHOKE BALLAST

CB 2.5 kW
Standard: L2.76635.0

Technical Data: Size (HxWxL): 358 x 243 x 450 mm. Weight: 55 kg. Protection Class: IP 22

Accessories: 15 m 2.5 kW Head to Ballast Cable L2.7562.0; 15 m 2.5 k